

Carr. 869, Calle 4 Las Palmas Industrial Park, Cataño, Puerto Rico 00962

Tel. 787-641-2420

## **Sterling Cake Display Case**







SBD-48-56-R



SBD-60-56-R

## **Features**

- Refrigeration system maintains temperatures between 36°F and 43°F (2°C to 6°C).
- Exterior: Stainless steel floor and walls, standard.
- Sliding doors.
- 12V **LED lighting** system, safe for users to operate.
- Tempered glass to avoid injury by broken glass.
- Preinstalled hidden caster design.
- Refrigerant: HYDRO-CARBON R290.
- **Shelves:** Adjustable glass shelves provide extra large viewing area to maximize bakery product presentation.
- Electronic control system makes it easy to adjust temperature set point and defrost frequency.
- Removable installation board makes it easy to access condenser coil for cleaning and service.
- NSF-7 compliant for open food product.

## **Technical Data**

Model	Doors	Shelves	Dimensions WxDxH inch	Capacity cu.ft.	НР	Amps	Voltage	Plug Type
SBD-36-56-R	2	2	35 3/8 × 28 3/4 × 47 1/4	11.3	1/3+	5.16	115/60/1	NEMA 5-15P
SBD-48-56-R	2	2	47 1/4 × 28 3/4 × 47 1/4	14	1/3+	5.64	115/60/1	NEMA 5-15P
SBD-60-56-R	2	2	59 1/8 × 28 3/4 × 47 1/4	21.2	1/2+	6	115/60/1	NEMA 5-15P

## Certifications







